



Technical Data Sheet

Naturaqua Extra Strong Wood Cleaner

Super-intensive terrace-deck
detergent

Code 0091



DESCRIPTION

Extra strong water-based cleaner, suitable for intensive degreasing treatments in the context of extraordinary maintenance. The product is indicated for removing stubborn dirt, greasy deposits, moulds, dark patinas, residues of old oils and impregnating agents even on large areas.

If diluted in water it allows for a more gentle cleaning, such as preliminary degreasing treatments on exotic woods. In this case it is recommended to dilute the product 1:1 with water. Wet the support with plenty of water before treatment.

It can alter the natural color of the wood making it darker. To restore the original color of the wood, use Exterior Wood Cleaner.

YIELD

5-10 m²/Lt depending on the conditions and type of substrate to be treated.

FIELDS OF APPLICATION

Wooden terraces, garden furniture, boat decks, pool edges; in general, outdoor wooden surfaces if grayed, dirty and with traces of old oil or impregnating treatments.

CERTIFICATIONS AND CONFORMITY

EN71.III Certification- Safe for children's toys Certification for green building issued by the Rosenheim **IBR** institute.
French **VOC Class A+** Conformity

CLEANING AND DILUTION

Ready to use product. It can be diluted with water if needed.

Characteristics	UM	Value
Density	g/ cm ³	1.13 ± 0.01
Viscosity Ford#4	sec.	60 ± 2
pH		11.8 ± 0.1



Action time (20°C)

min.

15-30

SURFACE PREPARATION

Wet the surface to be treated abundantly with water in order to slow down the drying of the detergent and prolong its action. It is recommended not to carry out the treatment with temperatures below 10°C or above 35°C.

HOW TO USE



Apply with a brush (preferably synthetic) in a slight excess, forming an abundant layer.



Leave on for 15-30 min.



Ensure surface remains wet, spraying gently with water if necessary or reapplying a small amount of product.



Massage the surface with a stiff synthetic brush.



Rinse thoroughly with water, with the help of a high pressure pump.



Wait until the substrate is completely dry before applying a finishing product.

TECHNICAL RECOMMENDATIONS

Shake well before use.

Wear protective gloves.

Preferably use synthetic bristle brushes and brushes.

After drying and sanding, the overpainting with water-based products is not recommended.

It is advisable not to apply in direct sunlight, on hot surfaces, in the presence of strong winds, rain, fog or with the risk of night frosts.

Carry out a preliminary test on a hidden area to check if the final effect corresponds to the desired one.

RECOMMEDED CYCLES

To complete the work cycle, the following products are recommended:

1. **Exterior Wood Cleaner** – cod. 0075 as a neutralizing cleaner
2. **Terrace Oil** – code 4971-IL as finishing oil for terraces
3. **Teak Oil** – cod.0360 as treatment oil for garden furniture
4. **Decking Oil HD** (code 4971XX) or **Decking Oil 2K** (code 49712K)

PACKAGING

Code 0091	12 x 1 Lt
Code 0092	2 x 5 Lt
Code 0093	1 x 10 Lt
Code 0094	1 x 25 Lt

STORAGE

Keep in a cool and well-ventilated place; keep container closed when not in use.

Keep from freezing.

The product has a storage time of 24 months from the production date.

WARNING

Read the SDS before use.

Observe the safety regulations in force.

Product for professional use.

Our technical data sheets are drawn up on the basis of the average results of our tests. However, our technical advice is given in good



Exterior Line

WATER BASED



faith but without warranty. In fact, different substrates, application conditions, systems, dilutions are an integral part of the final result and often beyond any control. The user must try the products supplied to check if they are suitable for his needs. For our part, we

guarantee the continuity of the chemical-physical characteristics.

Product code: **0091**
Revision: **04 of 11.06.2025**